



2 MILLION CANDLE POWER SPOTLIGHT 41-1085



USER INSTRUCTIONS - YOU MUST FULLY CHARGE THE BATTERY BEFORE FIRST USE.

Take care to read this guide carefully before using this product to avoid unnecessary damage to the unit.

SPECIAL FEATURES

Bright: 2 Million Candle Power beam carries up to one mile

Built-in 6V4AH sealed lead acid rechargeable battery

Charge in vehicle with car cord or at home with AC adaptor (both included)

A rubber cover to protect the charging hole

CHANGING THE BATTERY

Remove rubber bezel of the light head and loosen the 9 screws. 2 of the 9 screws are located under the rubber grip. The rubber grip is partially glued so you will have to pull forcefully on the rubber grip. Open the spotlight body and remove wires from battery and replace with new 6V 4.5AH battery. Reattach wires to battery (red to red, black to black). Hold wires against battery and reassemble spotlight replacing screws.

CHANGING THE BULB

Before changing the bulb, switch off the spotlight and let it cool for at least 10 minutes.

NEVER touch halogen bulb with bare hands (natural oils from hands could damage the bulb – you can use rubbing alcohol to wipe clean bulb)

Steps in changing the bulb:

Remove rubber bezel of the light head and loosen the 9 screws. 2 of the 9 screws are located under the rubber grip. The rubber grip is partially glued so you will have to pull forcefully on the rubber grip. Open the spotlight body and remove the split pin on the band of the reflector. Loosen the screw and remove the bulb by rotating bulb base, disconnect white lamp wire from the holder and reconnect with new H3-6V 100W Quartz Halogen bulb. Repeat the above steps in reverse order to reassemble spotlight.

OPERATING INSTRUCTIONS

Depress trigger to turn spotlight “ON”. The spotlight will stay “ON” while pushing the “trigger hold” rod sideways. A full charge will give you up to 20 minutes continuous operation. Release the “trigger hold” rod to turn spotlight “OFF”.

CHARGING – – DO NOT USE OR TURN ON SPOTLIGHT WHILE CHARGING

Remove black rubber jack cover by pulling on right side of the cover

AC Charging *With AC adaptor: Insert the AC plug into the jack at the back and the other end into an AC outlet. The LED indicator light will go on indicating that the spotlight is charging (approximately 15 hours).

DO NOT OVER CHARGE (do not leave spotlight charging for longer than specified charge time), battery can be damaged.

DC charging *With DC adaptor: Insert the DC plug into the jack at the back and insert the cigarette lighter plug into a car cigarette lighter socket. The LED indicator light will go on indicating that the spotlight is charging (approximately 12 hours). **DO NOT OVER CHARGE (do not leave spotlight charging for longer than specified charge time),** battery can be damaged.

The LED indicator will NOT turn off when spotlight is fully charged. It is merely a charging indicator.

DISCONNECT SPOTLIGHT AFTER CHARGING IS COMPLETED.

IMPORTANT SAFETY INSTRUCTIONS

NEVER touch lens while in use. Danger of high heat at the lens surface

NEVER look directly into light or shine in someone else’s eye

NEVER touch halogen bulb with bare hands (natural oils from hands could damage the bulb)

NEVER use the spotlight in water or close to fire

NEVER leave spotlight unattended during use

KEEP AWAY from children

ONLY use the accompanied AC or DC charger to recharge spotlight

Warranty: (Excluding bulbs and batteries) This product is warranted to be free from defect in material or workmanship for one year from date of purchase. If product is defective, please return to Dorcy for repair or replacement. Dorcy reserves the right to substitute product of equal value if returned product is not available.